



ANDALAN ALARM KEBAKARAN

Addressable Control Panel

MC-1600 Series



Characteristics /

- * Each loop can connect up to 250 addressable devices. Maximum networking are 32 loops and total addressable points are 8000.
- * Large LCD screen (40 x 15 lines) allows more events to be displayed on the same screen.
- * Loop device can be set up to be temporarily isolated.
- * Individual loop module test feature to save time on panel test.
- * On-board Self-test feature for simulating alarm output.
- * Easy system programming through PC to panel.
- * Events log can store up to 2030 events.
- * Specification optional thermal printer that can printout complete panel status.

Approvals:

Specifications /

Model	MC-1600 (1 ~ 8 Loop)	Remark
Power	220V AC 50/60Hz	Others also available
Battery Capacity	24V DC 4Ah	
Charging Voltage, Current	26V DC 100~1000mA	With auto adjustment function
Zone Voltage, Current	26.5V DC 340mA	
System Capacity	250 devices/1 loop	Expandable for site requirement
Exterior Resistance	Round-trip under 40Ω	
Transmitting Method	Digital series transmitting	
Accumulation Time	0~40 seconds	Other options available
Main Sound	85dB @1M	
Material	1.6mm steel plate	
Color	Pearl gray / Red signal	
Dimensions	1~4 loop : 400 x 500 x 130 mm 5~8 loop : 600 x 500 x 150 mm	